

View Online at <https://aerobasegroup.com/nsn/5962-01-015-0275>

Body Length:

Between 0.660 inches and 0.785 inches

Body Width:

Between 0.220 inches and 0.280 inches

Body Height:

Between 0.140 inches and 0.180 inches

Maximum Power Dissipation Rating:

750.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and hermetically sealed and negative outputs and positive outputs and w/enable and w/field effect transistor switch

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

4 channel

Design Function And Quantity:

1 driver, switch, field effect transistor

Case Outline Source And Designator:

T0-116 joint electron device engineering council

Terminal Surface Treatment:

Tin

Voltage Rating And Type Per Characteristic:

2.0 volts power source

Time Rating Per Characteristic:

300.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0