## NSN 5962-01-015-1160

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-015-1160

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+100.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and negative outputs and positive outputs and high speed and externally compensated
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
5 input
Design Function And Quantity:
1 amplifier, operational, high speed
Case Outline Source And Designator:
T0-100 joint electron device engineering council
Terminal Surface Treatment:
Tin
Voltage Rating And Type Per Characteristic:
15.0 volts power source
Time Rating Per Chacteristic:
300.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
94117-321012 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:

A458a0