## NSN 5962-01-015-3643

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-015-3643 **Body Length:** 0.808 inches **Body Width:** 0.294 inches **Body Height:** 0.194 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and positive outputs and high speed and bipolar and presettable and w/decoded output and w/open collector and w/enable and w/buffered output and w/disable and w/storage and programmed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Criticality Code Justification:** Feat **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -1.5 volts power source and 5.5 volts power source **Time Rating Per Chacteristic:** 50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Special Features:** Static electricity sensitive **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a

**Demilitarization:** Yes - demil/mli

**Unit Of Measure:** 

## NSN 5962-01-015-3643

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0