# NSN 5962-01-016-5296

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-016-5296

# **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

# **Body Height:**

Between 0.165 inches and 0.185 inches

# **Maximum Power Dissipation Rating:**

300.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

# Storage Tempurature Range:

-65.0/+150.0 degrees celsius

# **Features Provided:**

Monolithic and hermetically sealed and negative outputs and positive outputs and high gain and internally compensated

# **Inclosure Material:**

Glass and metal

# **Inclosure Configuration:**

# Can

**Input Circuit Pattern:** 

2 input

# **Design Function And Quantity:**

1 amplifier, wideband

# **Case Outline Source And Designator:**

T0-99 joint electron device engineering council

# **Terminal Surface Treatment:**

Gold

# Voltage Rating And Type Per Characteristic:

20.0 volts power source

# **Time Rating Per Chacteristic:**

50.00 nanoseconds propagation delay time, low to high level output

# **Precious Material And Location:**

Terminals gold

# **Precious Material:**

Gold

# **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

# **Terminal Type And Quantity:**

8 pin

# Shelf Life:

N/a

# Unit Of Measure:

---

# **Demilitarization:**

Yes - demil/mli

# NSN 5962-01-016-5296

Linear Microcircuit - Page 2 of 2

**Fiig:** A458a0

