# NSN 5962-01-016-7264

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-016-7264

## **Body Length:**

Between 0.365 inches and 0.385 inches

## **Body Width:**

Between 0.240 inches and 0.260 inches

## **Body Height:**

Between 0.035 inches and 0.070 inches

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+125.0 degrees celsius

## **Features Provided:**

Hermetically sealed and high speed and programmable and programmed and w/buffered output and w/decoded output and w/enable and

## 3-state output

Inclosure Material:

Ceramic

## Inclosure Configuration:

Flat pack

## **Output Logic Form:**

Transistor-transistor logic

### **Input Circuit Pattern:**

10 input

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

## **Time Rating Per Chacteristic:**

70.00 nanoseconds propagation delay time, low to high level output

## Memory Device Type:

Rom

#### **Memory Capacity:**

Unknown

## Test Data Document:

94117-310403 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

16 flat leads

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0