NSN 5962-01-017-1888

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-017-1888 **Body Length:** Between 0.740 inches and 0.830 inches **Body Width:** Between 0.275 inches and 0.310 inches **Body Height:** Between 0.050 inches and 0.180 inches **Maximum Power Dissipation Rating:** 900.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs and w/field effect transistor switch and bipolar **Inclosure Material:**

Inclosure Configuration:Dual-in-line

Input Circuit Pattern:

Ceramic and metal

2 channel

Design Function And Quantity:

4 driver, switch, field effect transistor and 4 switch, analog

Terminal Surface Treatment:

Tin

Time Rating Per Chacteristic:

130.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0