## NSN 5962-01-017-8416

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-017-8416

Body Length:
Between 0.740 inches and 0.780 inches
Body Width:
Between 0.240 inches and 0.275 inches
Body Height:
Between 0.135 inches and 0.165 inches
Maximum Power Dissipation Rating:
200.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+175.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and negative outputs and high speed and internally compensated
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Emitter-coupled logic
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 translator, level
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
10.0 volts power source
Time Rating Per Chacteristic:
12.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.)
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiia:

A458a0