

View Online at <https://aerobasegroup.com/nsn/5962-01-017-8416>

**Body Length:**

Between 0.740 inches and 0.780 inches

**Body Width:**

Between 0.240 inches and 0.275 inches

**Body Height:**

Between 0.135 inches and 0.165 inches

**Maximum Power Dissipation Rating:**

200.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+175.0 degrees celsius

**Features Provided:**

Monolithic and hermetically sealed and negative outputs and high speed and internally compensated

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Emitter-coupled logic

**Input Circuit Pattern:**

Quad 2 input

**Design Function And Quantity:**

4 translator, level

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

10.0 volts power source

**Time Rating Per Characteristic:**

12.00 nanoseconds propagation delay time, low to high level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0