## NSN 5962-01-019-8643

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-019-8643

view Offilite at https://defobasegroup.com/his//0302-01-013-00-3
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
140.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+175.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and negative outputs and high speed and internally compensated and w/enable and negative edge
triggered
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Emitter-coupled logic
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 flip-flop, r-s, clocked
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-10.0 volts power source
Time Rating Per Chacteristic:
6.00 nanoseconds propagation delay time, low to high level output
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli

**Fiig:** A458a0