

View Online at <https://aerobasegroup.com/nsn/5962-01-020-6661>

Body Length:

Between 0.690 inches and 0.710 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.160 inches and 0.180 inches

Maximum Power Dissipation Rating:

300.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and hermetically sealed and negative outputs and positive outputs and programmable and w/enable and externally compensated

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

4 channel

Design Function And Quantity:

4 amplifier, operational, general purpose

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

10.0 volts power source

Time Rating Per Characteristic:

20.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0