NSN 5962-01-020-6665

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-020-6665

view Online at https://defobasegroup.com/hsh/5502-01-020-0005
Body Length:
Between 0.690 inches and 0.830 inches
Body Width:
Between 0.275 inches and 0.310 inches
Body Height:
Between 0.050 inches and 0.180 inches
Maximum Power Dissipation Rating:
825.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and w/field effect transistor switch
Inclosure Material:
Ceramic and metal
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
5 channel
Design Function And Quantity:
1 driver, switch, field effect transistor and 1 switch, analog
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
25.0 volts power source
Time Rating Per Chacteristic:
10.00 nanoseconds propagation delay time, low to high level output and 10.00 nanoseconds propagation delay time, high to low leve
output
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:

A458a0