NSN 5962-01-020-6669

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-020-6669 **Body Length:** 0.400 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.155 inches and 0.180 inches **Maximum Power Dissipation Rating:** 800.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and high current and high speed and monolithic and positive outputs **Inclosure Material:** Ceramic and glass and metal **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 2 input **Design Function And Quantity:** 2 driver, high current and 2 driver, peripheral **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level output **Special Features:** Positive-or logic **Precious Material And Location:** Terminals gold **Precious Material:** Gold **Terminal Type And Quantity:** 8 printed circuit Shelf Life: N/a

Demilitarization: Yes - demil/mli

Unit Of Measure:

NSN 5962-01-020-6669

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0