NSN 5962-01-021-0856

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-021-0856

· · · · · · · · · · · · · · · · · · ·
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
42.6 milliwatts
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and externally compensated and synchronous and w/strobe
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
1 input
Design Function And Quantity:
1 shift register, static
Case Outline Source And Designator:
T0-100 joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
0.3 volts power source
Time Rating Per Chacteristic:
90.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Terminals gold
Test Data Document:
82577-932036 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-01-021-0856

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0