# NSN 5962-01-021-0857

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-021-0857

#### **Body Length:**

Between 0.660 inches and 0.785 inches

## Body Width:

Between 0.220 inches and 0.280 inches

## **Body Height:**

Between 0.140 inches and 0.180 inches

## **Maximum Power Dissipation Rating:**

65.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and bipolar and w/field effect transistor switch and monolithic

#### **Inclosure Material:**

Ceramic and glass

## Inclosure Configuration:

Dual-in-line

#### **Input Circuit Pattern:**

3 channel

### **Design Function And Quantity:**

1 switch, analog and 1 switch, field effect transistor

### Case Outline Source And Designator:

T0-116 joint electron device engineering council

### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

33.0 volts power source

#### Time Rating Per Chacteristic:

0.30 nanoseconds propagation delay time, low to high level output

#### Test Data Document:

82577-932381 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### Terminal Type And Quantity:

14 printed circuit

#### Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0