NSN 5962-01-021-1284

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-021-1284 **Body Length:** 0.440 inches **Body Width:** Between 0.245 inches and 0.285 inches **Body Height:** Between 0.045 inches and 0.085 inches **Maximum Power Dissipation Rating:** 260.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and edge triggered and w/clear and complementary outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 4 flip-flop, d-type, clocked **Case Outline Source And Designator:** F-5 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 16 flat leads **Specification Data:** 81349-mil-m-38510/17 government specification Shelf Life: N/a

Yes - demil/mli

Unit Of Measure:

Demilitarization:

NSN 5962-01-021-1284

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0