NSN 5962-01-021-2588

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-021-2588 **Body Length:** 2.000 inches **Body Width:** 1.000 inches **Body Height:** 0.400 inches **Maximum Power Dissipation Rating:** 600.0 milliwatts **Operating Tempurature Range:** -25.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and hybrid and complementary outputs and bipolar and negative outputs and positive outputs **Inclosure Material:** Resin **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 14 input **Design Function And Quantity:** 1 converter, digital to analog **Terminal Surface Treatment:** Gold **Time Rating Per Chacteristic:** 150.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminals gold **Precious Material:** Gold **Test Data Document:** 26512-gc852r drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig:

A458a0

Yes - demil/mli