

View Online at <https://aerobasegroup.com/nsn/5962-01-023-3269>

Body Length:

Between 0.371 inches and 0.409 inches

Body Width:

Between 0.247 inches and 0.283 inches

Body Height:

Between 0.050 inches and 0.075 inches

Maximum Power Dissipation Rating:

210.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Converter model 6514d fscm 35351

Features Provided:

Hermetically sealed and monolithic and positive outputs and asynchronous and synchronous and edge triggered

Inclosure Material:

Ceramic and metal

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

10 input

Design Function And Quantity:

2 flip-flop, j-k, master slave

Time Rating Per Characteristic:

22.00 nanoseconds propagation delay time, low to high level output

Precious Material And Location:

Terminals gold

Test Data Document:

35351-151469 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0