

View Online at <https://aerobasegroup.com/nsn/5962-01-023-3269>

**Body Length:**

Between 0.371 inches and 0.409 inches

**Body Width:**

Between 0.247 inches and 0.283 inches

**Body Height:**

Between 0.050 inches and 0.075 inches

**Maximum Power Dissipation Rating:**

210.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Converter model 6514d fscm 35351

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and asynchronous and synchronous and edge triggered

**Inclosure Material:**

Ceramic and metal

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

10 input

**Design Function And Quantity:**

2 flip-flop, j-k, master slave

**Time Rating Per Characteristic:**

22.00 nanoseconds propagation delay time, low to high level output

**Precious Material And Location:**

Terminals gold

**Test Data Document:**

35351-151469 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0