

View Online at <https://aerobasegroup.com/nsn/5962-01-023-9930>

Body Length:

Between 0.755 inches and 0.785 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

Between 0.140 inches and 0.185 inches

Maximum Power Dissipation Rating:

275.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Pallet id

Features Provided:

Hermetically sealed and monolithic and bipolar and high speed and low power and schottky and w/decoded output and w/enable and w/open collector

Inclosure Material:

Ceramic or metal

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

12 input

Time Rating Per Characteristic:

55.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

26512-g-820uc1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0