NSN 5962-01-023-9931

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-023-9931

Body Length:						
0.390 inches						
Body Width:						
Between 0.235 inches and 0.280 inches						
Body Height:						
Between 0.045 inches and 0.085 inches						
Maximum Power Dissipation Rating:						
280.0 milliwatts						
Operating Tempurature Range:						
-55.0/+125.0 degrees celsius						
Storage Tempurature Range:						
-65.0/+150.0 degrees celsius						
End Application:						
An/tpb-1a						
Features Provided:						
Hermetically sealed						
Inclosure Material:						
Ceramic						
Inclosure Configuration:						
Flat pack						
Output Logic Form:						
Transistor-transistor logic						
Input Circuit Pattern:						
5 input						
Design Function And Quantity:						
1 latch, d, clocked						
Case Outline Source And Designator:						
F-2 mil-m-38510						
Terminal Surface Treatment:						
Tin						
Voltage Rating And Type Per Characteristic:						
5.5 volts power source and -1.5 volts power source						
Time Rating Per Chacteristic:						
2.00 nanoseconds propagation delay time, low to high level output and 44.00 nanoseconds propagation delay time, low to high level						
output						
Test Data Document:						
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification						
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain						
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).						
Terminal Type And Quantity:						

Shelf Life:

14 flat leads

Specification Data:

81349-mil-m-38510/15 government specification

N/a

NSN 5962-01-023-9931

Digital Microcircuit - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0