NSN 5962-01-024-0975

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-024-0975 **Body Length:** 0.785 inches **Body Width:** 0.280 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 130.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Pallet id **Features Provided:** Hermetically sealed **Inclosure Material:** Ceramic or metal **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 4 receiver, line **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** 30.0 volts power source **Time Rating Per Chacteristic:** 85.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminals gold

Test Data Document:

26512-g-820vs drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-024-0975

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0