NSN 5962-01-024-0975

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-024-0975

View Online at https://aerobasegroup.com/nsn/5962-01-024-0975
Body Length:
0.785 inches
Body Width:
0.280 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
130.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Pallet id
Features Provided:
Hermetically sealed
Inclosure Material:
Ceramic or metal
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
4 input
Design Function And Quantity:
4 receiver, line
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
30.0 volts power source
Time Rating Per Chacteristic:
85.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminals gold
Test Data Document:
26512-g-820vs drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, et
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-024-0975

Linear Microcircuit - Page 2 of 2

Fiig: A458a0

