NSN 5962-01-024-2932

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-024-2932

view Online at https://aerobasegroup.com/nsn/5962-01-024-2932
Body Length:
Between 0.235 inches and 0.265 inches
Body Width:
Between 0.140 inches and 0.265 inches
Body Height:
Between 0.033 inches and 0.070 inches
Maximum Power Dissipation Rating:
300.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Horizontal display p/n 110150-13 fscm 10138
Features Provided:
Hermetically sealed
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
12.0 volts power source
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
10138-50260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-01-024-2932

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0