

View Online at <https://aerobasegroup.com/nsn/5962-01-024-9518>

**Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

**Body Height:**

Between 0.165 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

330.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Guided missile

**Features Provided:**

Hermetically sealed and monolithic and externally compensated

**Inclosure Material:**

Metal

**Inclosure Configuration:**

Can

**Input Circuit Pattern:**

2 input

**Design Function And Quantity:**

1 amplifier, operational, general purpose

**Case Outline Source And Designator:**

A-1 mil-m-38510

**Terminal Surface Treatment:**

Tin

**Voltage Rating And Type Per Characteristic:**

20.0 volts power source and -20.0 volts power source

**Time Rating Per Characteristic:**

20.00 nanoseconds propagation delay time, low to high level output

**Special Features:**

Power source dc in volts and polarity

**Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 wire lead

**Specification Data:**

81349-mil-m-38510/101d government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0