NSN 5962-01-024-9520

Linear Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/hsn/5962-01-024-9520
Body Outside Diameter:
Between 0.355 inches and 0.370 inches
Body Height:
Between 0.235 inches and 0.255 inches
Maximum Power Dissipation Rating:
20.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Antenna coupler fscm 80058
Features Provided:
Hermetically sealed and monolithic and positive outputs
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
4 input
Design Function And Quantity:
1 amplifier, video and 1 amplifier, wideband
Terminal Surface Treatment:
Gold
Time Rating Per Chacteristic:
15.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Terminals gold
Test Data Document:
13499-351-1086 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A458a0