NSN 5962-01-025-1023

Linear Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/hsn/5962-01-025-1023
Body Length:
Between 0.750 inches and 0.785 inches
Body Width:
Between 0.240 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Misc sras p/n 247as10-100 fscm 30003
Features Provided:
Hermetically sealed and high gain and low power and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 amplifier, operational, general purpose and 2 amplifier, preamplifier
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Test Data Document:
30003-247as-c0918 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fila:

A458a0