## NSN 5962-01-025-1023

Linear Microcircuit - Page 1 of 1



| view Online at https://aerobasegroup.com/hsn/5962-01-025-1023  |
|--|
| Body Length:   |
| Between 0.750 inches and 0.785 inches  |
| Body Width:  |
| Between 0.240 inches and 0.280 inches  |
| Body Height:   |
| Between 0.140 inches and 0.185 inches  |
| Maximum Power Dissipation Rating:  |
| 500.0 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| End Application:   |
| Misc sras p/n 247as10-100 fscm 30003   |
| Features Provided:   |
| Hermetically sealed and high gain and low power and monolithic   |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Input Circuit Pattern:   |
| Dual 2 input   |
| Design Function And Quantity:  |
| 2 amplifier, operational, general purpose and 2 amplifier, preamplifier  |
| Case Outline Source And Designator:  |
| T0-116 joint electron device engineering council   |
| Terminal Surface Treatment:  |
| Solder   |
| Test Data Document:  |
| 30003-247as-c0918 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                      |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiia:  |

A458a0