## NSN 5962-01-025-1025

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-025-1025 **Body Length:** Between 0.740 inches and 0.780 inches **Body Width:** Between 0.240 inches and 0.270 inches **Body Height:** Between 0.135 inches and 0.165 inches **Maximum Power Dissipation Rating:** 750.0 milliwatts **Operating Tempurature Range:** -40.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** An/apm-30 (v) -3 **Features Provided:** Hermetically sealed and monolithic and w/buffered output **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 oscillator, voltage controlled **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 13.0 volts power source **Test Data Document:** 

97384-5339-093024 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

14 printed circuit

Shelf Life:

N/a

**Unit Of Measure:** 

## **Demilitarization:**

Yes - demil/mli

Fiig:

A458a0