

View Online at <https://aerobasegroup.com/nsn/5962-01-026-1395>

Body Length:

0.870 inches

Body Width:

0.250 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and w/strobe and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

Dual 2 input

Design Function And Quantity:

2 comparator, voltage

Terminal Surface Treatment:

Gold or tin

Voltage Rating And Type Per Characteristic:

36.0 volts power source

Time Rating Per Characteristic:

400.00 nanoseconds propagation delay time, low to high level output and 400.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminal surfaces option gold

Precious Material:

Gold

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0