NSN 5962-01-026-2459

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-026-2459 **Body Length:** 0.870 inches **Body Width:** 0.250 inches **Body Height:** 0.180 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Virginia class cgn (41), arleigh burke class ddg, spruance class dd (963), los angeles class ssn (688), ticonderoga class c (947), forrestal class cv, oliver perry class ffg, sturgeon class ssn (637), wasp class lhd, austin ship class lpd-4 amphibious transport docks. **Features Provided:** Programmable and high speed and expandable and w/open collector and w/enable **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Criticality Code Justification:** Feat **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Special Features:** Weapon system essential **Terminal Type And Quantity:**

N/a

16 printed circuit

Unit Of Measure:

Shelf Life:

NSN 5962-01-026-2459

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0