NSN 5962-01-026-2491

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-026-2491
Body Length:
0.896 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
55.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
An/fps
Features Provided:
Hermetically sealed and monolithic and schottky
Inclosure Material:
Glass or metal or ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
13 input
Design Function And Quantity:
1 gate, nand
Case Outline Source And Designator:
D-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.2 volts power source and 5.5 volts power source
Special Features:
Nuclear hardness critical items
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5962-01-026-2491

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0