## NSN 5962-01-026-6044

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-026-6044
Body Length:
Between 0.740 inches and 0.870 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.120 inches and 0.185 inches
Maximum Power Dissipation Rating:
625.0 milliwatts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Test set countermeasure fscm 94117
Features Provided:
Bipolar and monolithic and positive outputs and programmable and w/buffered output and w/disable and w/enable
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
6 input
Criticality Code Justification:
Feat
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
50.00 nanoseconds propagation delay time, low to high level output
Memory Device Type:
Rom
Memory Capacity:
Unknown
Special Features:
Weapon system essential
Terminal Type And Quantity:

N/a

16 printed circuit Shelf Life:

## NSN 5962-01-026-6044

Memory Microcircuit - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0