## NSN 5962-01-026-6045



Memory Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-026-6045 **Body Length:** Between 0.740 inches and 0.870 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.120 inches and 0.185 inches **Maximum Power Dissipation Rating:** 625.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Test set countermeasure fscm 94117 **Features Provided:** Bipolar and monolithic and positive outputs and programmable and w/buffered output and w/disable and w/enable **Inclosure Material:** Plastic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source **Time Rating Per Chacteristic:** 50.00 nanoseconds propagation delay time, low to high level output **Memory Device Type:** Rom

**Memory Capacity:** 

Unknown

**Terminal Type And Quantity:** 

16 printed circuit

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

Yes - demil/mli

## NSN 5962-01-026-6045

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0