NSN 5962-01-026-6051

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-026-6051
Body Length:
0.640 inches
Body Width:
Between 0.360 inches and 0.440 inches
Body Height:
Between 0.045 inches and 0.090 inches
Maximum Power Dissipation Rating:
795.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Tf-15a aircraft fscm 76301
Features Provided:
Hermetically sealed and monolithic and high speed
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
14 stage
Design Function And Quantity:
1 generator, function
Case Outline Source And Designator:
F-6 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
50.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
22 flat leads
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5962-01-026-6051

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0