## NSN 5962-01-026-8815

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-026-8815

Body Length:
Between 0.240 inches and 0.290 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.030 inches and 0.070 inches
Maximum Power Dissipation Rating:
200.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Gen purp digital cp
Features Provided:
Hermetically sealed and monolithic
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 amplifier, wideband
Case Outline Source And Designator:
T0-91 joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
-8.0 volts power source and 8.0 volts power source
Time Rating Per Chacteristic:
100.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Terminals gold
Test Data Document:
90536-7903505 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
10 flat leads
Shelf Life:
N/2

--

**Unit Of Measure:** 

## NSN 5962-01-026-8815

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0