NSN 5962-01-027-3779

Linear Microcircuit - Page 1 of 1

A458a0



| view Online at https://aerobasegroup.com/nsn/5962-01-027-3779 |
|--|
| Body Outside Diameter: |
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| Between 0.165 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 2.0 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Test position amplifier fscm 82577 |
| Features Provided: |
| Hermetically sealed and monolithic and positive outputs |
| Inclosure Material: |
| Metal |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| Dual 2 input |
| Design Function And Quantity: |
| 2 regulator, tracking and 2 regulator, voltage |
| Case Outline Source And Designator: |
| T0-5 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 5.5 volts power source |
| Test Data Document: |
| 81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 14 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |