

View Online at <https://aerobasegroup.com/nsn/5962-01-027-3781>

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

Between 0.165 inches and 0.185 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Signal processor fscm 15786

Features Provided:

Hermetically sealed and high speed and monolithic

Inclosure Material:

Metal

Inclosure Configuration:

Can

Input Circuit Pattern:

Dual 2 input

Design Function And Quantity:

2 comparator, voltage

Case Outline Source And Designator:

T0-5 joint electron device engineering council

Terminal Surface Treatment:

Tin

Time Rating Per Characteristic:

80.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0