NSN 5962-01-028-0490

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-028-0490
Body Length:
Between 0.750 inches and 0.785 inches
Body Width:
Between 0.245 inches and 0.271 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
630.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+125.0 degrees celsius
End Application:
Receiver/transmitter set fscm 52483
Features Provided:
Hermetically sealed and monolithic and bipolar and negative outputs and positive outputs and w/enable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
3 channel
Design Function And Quantity:
3 driver, line
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
1.5 volts power source and 6.0 volts power source
Time Rating Per Chacteristic:
320.00 nanoseconds propagation delay time, low to high level output
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Ves - demil/mli

Fiig:

A458a0