NSN 5962-01-028-4176

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-028-4176

Body Length:
Between 0.370 inches and 0.400 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.135 inches and 0.155 inches
Maximum Power Dissipation Rating:
625.0 milliwatts
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Storage Tempurature Range:
-55.0/+125.0 degrees celsius
End Application:
Kit-load boxes fscm 98897
Features Provided:
Monolithic and high speed and internally compensated and negative outputs and positive outputs
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-30.0 volts power source and 30.0 volts power source
Time Rating Per Chacteristic:
0.25 nanoseconds propagation delay time, low to high level output
Terminal Type And Quantity:
8 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0