

View Online at <https://aerobasegroup.com/nsn/5962-01-028-6134>

Body Length:

Between 0.755 inches and 0.785 inches

Body Width:

Between 0.265 inches and 0.291 inches

Body Height:

Between 0.159 inches and 0.199 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Nato seasparrow sms fscm 49956

Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs and bipolar and programmable and programmed and w/buffered output and w/enable and wire-or outputs

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

6 input

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

Time Rating Per Characteristic:

50.00 nanoseconds propagation delay time, low to high level output

Memory Device Type:

Rom

Memory Capacity:

Unknown

Test Data Document:

10001-2891641 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0