NSN 5962-01-028-6942

Linear Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/hsn/5962-01-026-6942
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.160 inches and 0.180 inches
Maximum Power Dissipation Rating:
680.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
An/tpn-19 fscm 49956
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs and w/strobe
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
3 input
Design Function And Quantity:
1 amplifier, sense
Case Outline Source And Designator:
T0-99 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-5.0 volts power source and 5.0 volts power source
Time Rating Per Chacteristic:
30.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
49956-461653 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Fiig: A458a0

Yes - demil/mli