

View Online at <https://aerobasegroup.com/nsn/5962-01-028-6961>

**Body Length:**

Between 0.750 inches and 0.785 inches

**Body Width:**

Between 0.245 inches and 0.271 inches

**Body Height:**

Between 0.140 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

76.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Signal processor fscm 15786

**Features Provided:**

Hermetically sealed and high speed and monolithic and positive outputs and schottky

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Design Function And Quantity:**

4 gate, and

**Time Rating Per Characteristic:**

12.00 nanoseconds propagation delay time, low to high level output

**Test Data Document:**

81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0