## NSN 5962-01-028-6967

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-028-6967

## **Body Length:** 0.896 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Audio switch unit model as-1920 fscm 15942 **Features Provided:** Hermetically sealed and monolithic and positive outputs and w/enable and programmed and w/complement and w/open collector **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 1 converter, code binary coded decimal to binary **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source **Time Rating Per Chacteristic:** 40.00 nanoseconds propagation delay time, low to high level output **Test Data Document:** 15942-0213-1-1028 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:**

16 printed circuit

Shelf Life:

N/a

## Unit Of Measure:

- **Demilitarization:**
- Yes demil/mli

## NSN 5962-01-028-6967

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

