

View Online at <https://aerobasegroup.com/nsn/5962-01-029-5083>

**Body Length:**

0.440 inches

**Body Width:**

0.285 inches

**Body Height:**

0.085 inches

**Maximum Power Dissipation Rating:**

715.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Programmed and monolithic

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Flat pack

**Input Circuit Pattern:**

10 input

**Current Rating Per Characteristic:**

125.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

85.00 nanoseconds propagation delay time, high to low level output and 85.00 nanoseconds propagation delay time, low to high level output

**Memory Device Type:**

Prom

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0