NSN 5962-01-029-7349

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-029-7349

view Offiline at https://aerobasegroup.com/hish/0302-01-023-7040
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
An/wlr-11a fscm 33472
Features Provided:
Hermetically sealed and hybrid and w/field effect transistor switch and high speed and negative outputs and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
2 channel
Design Function And Quantity:
2 switch, analog
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
6.0 volts power source
Test Data Document:
81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Fiig: A458a0

Demilitarization: Yes - demil/mli