NSN 5962-01-029-9117

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-029-9117
Body Length:
Between 0.240 inches and 0.260 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.030 inches and 0.070 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Data display group type an/uya- (v)
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs and w/strobe
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 comparator, voltage, differential
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
15.0 volts power source
Time Rating Per Chacteristic:
300.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
05869-710205-688 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawin
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
10 flat leads
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli

Fiig: A458a0