NSN 5962-01-029-9125

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-029-9125 **Body Length:** 0.265 inches **Body Width:** 0.265 inches **Body Height:** Between 0.030 inches and 0.080 inches **Maximum Power Dissipation Rating:** 30.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+200.0 degrees celsius **End Application:** Data display group type an/uya- (v) **Features Provided:** Hermetically sealed and monolithic and positive outputs and w/clear and w/storage **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 5 input **Design Function And Quantity:** 1 register, storage **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 35.00 nanoseconds propagation delay time, low to high level output **Test Data Document:** 05869-717360-5 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 flat leads Shelf Life: N/a **Unit Of Measure:**

Yes - demil/mli

Demilitarization:

NSN 5962-01-029-9125

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0