NSN 5962-01-029-9331

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-029-9331

| view Online at https://aerobasegroup.com/nsn/5962-01-029-9551 |
|--|
| Body Length: |
| Between 0.680 inches and 0.760 inches |
| Body Width: |
| Between 0.235 inches and 0.265 inches |
| Body Height: |
| Between 0.090 inches and 0.110 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and low power and resettable and retriggerable |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| Dual 3 input |
| Design Function And Quantity: |
| 2 multivibrator, monostable |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts power source and 7.0 volts power source |
| Test Data Document: |
| 10001-2064892 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 16 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |