NSN 5962-01-030-2095

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-030-2095 **Body Length:** 0.260 inches **Body Width:** 0.260 inches **Body Height:** Between 0.050 inches and 0.065 inches **Maximum Power Dissipation Rating:** 1.5 watts **Operating Tempurature Range:** +0.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** P-1166/uya-4v fscm 05869 **Features Provided:** Hermetically sealed and high speed and hybrid and negative outputs and positive outputs and 2-phase **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 driver, clock **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -1.5 volts power source and 5.5 volts power source **Time Rating Per Chacteristic:** 12.00 nanoseconds propagation delay time, low to high level output **Test Data Document:** 05869-710255-52 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 10 flat leads Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0