## NSN 5962-01-030-2107

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-030-2107 **Body Length:** 2.000 inches **Body Width:** 0.500 inches **Body Height:** 0.170 inches **Operating Tempurature Range:** -0.0/+70.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius **End Application:** Multiplexer fscm 52483 **Features Provided:** Hermetically sealed and positive outputs and asynchronous and edge triggered and resettable and synchronous and w/disable and w/enable and w/storage and w/strobe and 3-state output **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 34 input **Design Function And Quantity:** 1 transmitter **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 0.3 volts power source **Time Rating Per Chacteristic:** 500.00 nanoseconds propagation delay time, low to high level output **Test Data Document:** 52483-800176 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 40 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig: A458a0

Yes - demil/mli